

2332 Cathy Lane Jasper, Indiana 47546 800.876.2120 812.482.9318 Fax www.versteel.com

۵

Thank you for your purchase. Versteel® hopes that you have many great years of use from this table and from all of our products. If you have questions that these instructions don't answer, please call customer service at 800.876.2120.



DOCUMENT CONTAINS 1 PAGE	ASSEMBLY INSTRUCTIONS : TY FOLDING TABLE LEGS
COMPONENTS: A TABLE TOP (1 QTY) B LEG/FOLDING PAN ASSEMBLY (2 QTY) C SCREWS (24 QTY)	TOOLS REQUIRED: POWER DRILL/DRIVER WITH ADJUSTABLE TORQUE
ASSEMBLY : STEP 1 PLACE THE TOP FACE DOWN ON THE FLOOR. (MAKE SURE THE FLOOR IS CLEAN AND FREE OF ANY DEBRIS.) ASSEMBLY : STEP 2 LOCATE THE BASE PRE-DRILLS ON THE TOP. TYPICALLY THE HOLES FOR THE FOUR (4) CORNERS OF EACH FOLDING PAN WILL HAVE PRE-DRILLS ON THE TOPS. (DIAGRAM 1) PLACE LEG ASSEMBLIES OVER THE PRE-DRILLS. VERIFY THE CORRECT BASE ORIENTATION. (DIAGRAM 2)	(4) OUTER HOLES OF TOP PLATE ARE PRE-DRILLED IN TOP FOR LOCATING
NOTE: WHEN INSTALLING BASES, IT IS ABSOLUTELY CRITICAL THAT THE TORQUE SETTING ON THE POWER DRIVER BE AT THE LOWEST LEVEL NECESSARY TO SET THE SCREWS IN ALL THE WAY. OVER- TORQUEING SCREWS WILL RESULT IN "STRIPPED-OUT" SCREWS, AND BASES MAY PULL AWAY FROM TOP WHILE IN USE. THIS IS ESPECIALLY COMMON WHEN HIGH- VOLTAGE POWER DRIVERS ARE USED WITH CLUTCH SETTING ON "DRILL/DRIVER." IT IS THE RESPONSIBILITY OF INSTALLER TO ENSURE THAT PROPER TORQUE SETTINGS ARE USED TO PREVENT STRIPPED-OUT SCREWS.	

ASSEMBLY INSTRUCTIONS : TY FOLDING TABLE LEGS

